Hybrid Reader EDM - 9600 Series

Overview:


A hybrid insertion type card reader that decodes up to three tracks of magnetic data as well as reads/writes to smart cards. This industry standard footprint reader is used throughout the world in self-service, payphone and banking applications for more than a decade. This reader has the lower power consumption compared to the solenoid locking system and provides reliability and durability in any self-service application.

Features:

- Triple DES Encryption
- Mag Stripe Card Read
- IC Contact Card Read/Write
- ❖ T=0, T=1 Protocol
- Easy to Upgrade Firmware
- 1 x SAM / 4 x SAM module (option)
- LED Indicators
- Motor Locking
- EMV Level 1


Applications:

- ATM / Cash Dispenser
- Vending Machine
- Kiosk (information & payment)
- POS System



Technical Specifications:

Card Standard	Magnetic - ISO-7810, 7811; IC - ISO-7816
Power	DC 5V \pm 5%
Communication	TTL / RS-232C / USB
Life Time	Mag Head: Min. 500,000 cycles; IC Contacts: Min. 700,000 contacts
Environment	Operation: 5 ~ 50°C / 0 ~ 90% RH; Storage: -20 ~ 70°C / 0 ~ 90% RH
Dimensions	99 x 73 x 120 mm



5150 Campus Drive · Plymouth Meeting, PA 19462 · USA Tel: 610-825-7090 · 1-800-523-0253 · Fax: 610-834-7708 E-mail: sales@pdiscan.com · Internet: www.pdiscan.com