# Hybrid Reader EDM - 9800 Series

#### **Overview:**

A manual insertion type of MS & IC card reader that reads up to three tracks of MS data and reads/writes IC card. It can be easily programmed & configured to match application and communication requirements from customers. It combines MS & IC card reading capabilities into a compact solution and will be your ideal choice for demanding OEM applications.

### Features:

- Triple DES Encryption
- Mag Stripe Card Read
- IC Contact Card Read/Write
- ✤ T=0, T=1 Protocol
- Easy to Upgrade Firmware
- ✤ USB Interface & USB Powered (5V)
- LED Indicators
- Solenoid Locking
- EMV Level 1

## **Applications:**

- ATM / Cash Dispenser
- Vending Machine
- Kiosk (information & payment)
- POS System



## **Technical Specifications:**

Card Standard	Magnetic - ISO-7810, 7811; IC - ISO-7816
Power	DC 5V $\pm$ 5%
Communication	TTL / RS-232C / USB
Life Time	Mag Head: Min. 500,000 cycles; IC Contacts: Min. 700,000 contacts
Environment	Operation: 5 ~ 50°C / 0 ~ 90% RH; Storage: -20 ~ 70°C / 0 ~ 90% RH
Dimensions	99 x 73 x 120 mm



5150 Campus Drive · Plymouth Meeting, PA 19462 · USA Tel: 610-825-7090 · 1-800-523-0253 · Fax: 610-834-7708 E-mail: sales@pdiscan.com · Internet: www.pdiscan.com