

PD8634 RF and Barcode Access Control Time & Attendance PoE Ethernet



Model	PD8634
Dimensions	86mm * 103mm * 20mm
Material	PC + Armored Glass
Weight	130g
Voltage	DC 12V (5V – 30V)
Current	<150mA 12V power supply
Communication Port	PoE Ethernet
Image Sensor	640 x 480 CMOS, 30fps
Perspective	Horizontal 63', Vertical 51'
Reading Angle	Roll: 360', Pitch: ± 60', Skew: ± 50'
Reading Code System	On by default: EAN13, EAN8, UPC-A, UPC-EO, UPC-E1, Code 128, Code 39, Code 93, CodaBar, QR Code, PDF417, DataMatrix Off by default, Interleaved 2 of 5, Industrial 25, Matrix 2 of 5, Code 11, MSI Plessey, RSS-14, RSS-Limited, RSS-Expanded
Reading Distance	30 – 230mm (6-inch mobile phone, WeChat QR payment code)
Reading Accuracy	1D: ≥ 5mil / 2D: ≥ 10mil
Symbol Contrast	≥ 25%
Recognition Pattern	Active / passive, with support for induction mode
Sweep Code Feedback	Beeping: the light indicates scanning code
Card Swipe Support	ISO14443A / B, support ID card physical ID, NFC mobile phone card, Mifare card
Operating Temperature	-20°C ~ 60°C
Operating Humidity	5%RH~95%RH (Non-Condensing)
Storage Temperature	-40°C ~ 80°C
Ambient Lighting	0-80000Lux
Electrostatic Protection	Contact discharge ± 6KV and air discharge ± 12KV
IP Protection	Front IP54



5150 Campus Drive • Plymouth Meeting, PA 19462 • USA
 Tel: 610-825-7090 • 1-800-523-0253 • Fax: 610-834-7708
 E-mail: sales@pdiscan.com • Internet: www.pdiscan.com